

313243 FTL8G9

GAS GRIDDLE WITH SMOOTH PLATE TOP



- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Sloped Inclined cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Sloped Inclined cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.



TECHNICAL DATA

TOTAL POWER	16 kW	GAS POWER	16 kW
NATURAL GAS CONSUMPTION	1,69 m³/h	LPG CONSUMPTION	1.26 m³/h
COOKING SURFACE	74,9x69,8 cm	PLATE TYPE	Smooth
HEATING ZONES	n° 2	CE GAS CERTIFICATE NUMBER	CE-0085BO0093
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	35 mm
GAS CONNECTION HEIGHT (X)	766 mm	GAS CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
WIDTH	80 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	87 cm
PACKAGE DEPTH	101 cm	PACKAGE HEIGHT	56 cm
NET WEIGHT	107,5 kg	GROSS WEIGHT	119,5 kg
VOLUME	0,49 m³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	6400.0 W	SENSIBLE HEAT RELEASE	5600.0 W
STEAM RELEASE	9408.0 g/h		

ACCESSORIES

120595 GRIDDLE-CLEANING SCRAPER

120597 SCRAPER - SPARE BLADE KIT (10 PCS)

399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)



INSTALLATION SCHEMES

