

---

**316128****PIW4FE9****FREESTANDING WOK INDUCTION BOILING TOP ON  
OPEN CABINET**

---



- Freestanding wok induction boiling top (40 cm) on an open cabinet.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Glass ceramic top (Ø 30 and 6 mm thick) hermetically sealed to the top for maximum hygiene and ease of cleaning.
- 5 kW single area.
- Power regulator 0-6-infinite.
- Increased heating speed compared to other wok types.
- Heating is enabled only when in contact with the pan, saving energy and reducing overheating.
- Front air filter drawer easily accessible for cleaning and replacement.
- LED light for detecting pans and signalling operation and errors.
- To optimise efficiency, use high-quality induction wok pans.
- Technical compartment for easy connection to the electrical network.
- Avoid placing above ovens or refrigerated bases.

TECHNICAL DATA

TOTAL POWER	5 kW	ELECTRIC POWER	5 kW
CAMPO_0002	50/60	CAMPO_0003	400 3N ~
CAMPO_0142	1x5	CAMPO_0076	0007
CAMPO_0146	0004	CAMPO_0138	4 x 1,5
CAMPO_0139	H07 RN-F	CAMPO_0079	0001
CAMPO_0165	35	CAMPO_0166	329
CAMPO_0167	-75	CAMPO_0185	15
CAMPO_0186	15/25	CAMPO_0187	4
WIDTH	40 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	101 cm
PACKAGE DEPTH	46,0 cm	PACKAGE HEIGHT	115,0 cm
CAMPO_0061	43	CAMPO_0062	55,5
CAMPO_0063	0,53	CAMPO_0064	84198180

ACCESSORIES

- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 319009 REAR COVERING PANEL FOR CABINET (L=40CM)
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES

