

316269

FTL8FE9

## FREESTANDING ELECTRIC GRIDDLE WITH SMOOTH PLATE ON OPEN CABINET



- Freestanding electric griddle with a smooth steel cooking plate on an open cabinet (80 cm).
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- 2 independent cooking zones.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- $\bullet$  Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.



TECHNICAL DATA			
TOTAL POWER	12 kW	ELECTRIC POWER	12 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	50÷320 °C	CABINET DIMENSIONS	77x76,1x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm²	COOKING SURFACE	74,9x69,8 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Smooth
HEATING ZONES	n° 2	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	86,0 cm	PACKAGE DEPTH	100,0 cm
PACKAGE HEIGHT	112 cm	NET WEIGHT	117,0000 kg
GROSS WEIGHT	139 kg	VOLUME	0,96 m <sup>3</sup>
HARMONISED CODE	84198180	LATENT HEAT RELEASE	4800.0 W
SENSIBLE HEAT RELEASE	3960.0 W	STEAM RELEASE	7056.0 g/h

## **ACCESSORIES**

120597 SCRAPER - SPARE BLADE KIT (10 PCS)

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

319010 REAR COVERING PANEL FOR CABINET (L=80CM)

399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)



## **INSTALLATION SCHEMES**

