

**316556**

**EHLD4BFE9**

**FREESTANDING ELECTRIC GRIDDLE WITH  
BRUSHED, CHROME-PLATED, SMOOTH PLATE AND  
ELECTRONIC CONTROL ON OPEN CABINET WITH  
EVENHEAT TECHNOLOGY**



- EVENHEAT Freestanding electric griddle on an open cabinet (40 cm) with electronic control and with a brushed chrome-plated smooth cooking plate to cook a variety of products: from meat to fish and vegetables.
- The electronic control allows for greater precision between the set temperature and the cooking plate temperature.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances product grilling.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Thanks to thin, flexible elements, heat is distributed with absolute precision exactly where it is needed.
- The EVENHEAT technology, patent pending, grants a real temperature across the full plate, eliminating any cold or overheated spots
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Included: removable splashback, cap and scraper.
- Technical compartment for easy connection to the electrical network.

---

## TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	CABINET DIMENSIONS	33x76,1x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm <sup>2</sup>	COOKING SURFACE	34,9x69,8 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Brushed chrome-plated - smooth
HEATING ZONES	n° 1	ELECTRICAL CONNECTION HEIGHT (H)	660 mm
ELECTRICAL CONNECTION HEIGHT (X)	321 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	40 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	45 cm	PACKAGE DEPTH	100 cm
PACKAGE HEIGHT	114 cm	NET WEIGHT	70 kg
GROSS WEIGHT	82 kg	VOLUME	0,53 m <sup>3</sup>
HARMONISED CODE	84198180		

---

## ACCESSORIES

- 120595 GRIDDLE-CLEANING SCRAPER
- 120597 SCRAPER - SPARE BLADE KIT (10 PCS)
- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 319009 REAR COVERING PANEL FOR CABINET (L=40CM)
- 319055 SIDE HEAT PROTECTION DEVICE
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)


**INSTALLATION SCHEMES**


Fig.1 | Abb.1 | pmc.1 - 5415.561.00