

**713182**

**FTRR8FG7**

## **FREESTANDING GAS GRIDDLE WITH RIBBED PLATE ON OPEN CABINET**



- Freestanding gas griddle with a ribbed steel cooking plate on an open cabinet (80 cm).
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- Heating through 2 2-branch chrome-plated steel burners (7 kW) with 2 independent working zones.
- Valved gas cock with maximum temperature of 390°C.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

---

## TECHNICAL DATA

TOTAL POWER	14 kW	GAS POWER	14 kW
NATURAL GAS CONSUMPTION	1,48 m³/h	LPG CONSUMPTION	1.1 kg/h
CABINET DIMENSIONS	73x57,4x39,5 cm	COOKING SURFACE	74,8x56,4 cm
PLATE TYPE	Ribbed	HEATING ZONES	n° 2
CE GAS CERTIFICATE NUMBER	CE-0085BO0093	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	660 mm	GAS CONNECTION HEIGHT (X)	766 mm
GAS CONNECTION HEIGHT (Y)	-63 mm	FOOT HEIGHT	155 mm
FOOT ADJUSTMENT	155/250 mm	WIDTH	80 cm
DEPTH	70 cm	HEIGHT	90 cm
PACKAGE WIDTH	85,0 cm	PACKAGE DEPTH	81 cm
PACKAGE HEIGHT	112 cm	NET WEIGHT	87,5000 kg
GROSS WEIGHT	105,8000 kg	VOLUME	0,76 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	5600.0 W
SENSIBLE HEAT RELEASE	4900.0 W	STEAM RELEASE	8232.0 g/h

---

## ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
719005	TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=80CM)
799503	SIDE COVERING PANEL FOR FREESTANDING MODULE
799506	PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.649.00