MOSAICO74



716111

PCM4FE7

FREESTANDING ELECTRIC BOILING TOP WITH 1 SQUARED HERMETIC PLATE (22X22 CM - 8.7X8.7 IN) ON OPEN CABINET

• Freestanding electric boiling top with 1 squared plate on an open cabinet (40x45 cm).

 \bullet Mosaico74 is a special line of modular units, only 45 cm deep, which combine

perfectly with the Tecno74 range to create compact cooking islands designed to make the best use of space.

• AISI 304 stainless steel worktop (15/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.

 \bullet AISI 304 stainless steel control panel. Stainless steel side and back panels.

• Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.

• Cast iron squared electric plates (22x22) hermetically fixed to the deep drawn worktop.

- 2.6 kW power for each plate adjustable to 6 levels.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each plate.
- Lights warning when the plates are ignited.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

TECHNICAL DATA

TOTAL POWER	2,6 kW	GAS POWER	- kW
ELECTRIC POWER	2,6 kW	FREQUENCY	50 Hz
VOLTAGE	230 3 ~ V	BOILING TOP POWER	2,6 kW
COOKING ZONE POWER	1x2,6 n°- kW	ELECTRIC PLATE DIMENSIONS	22x22 cm
NUMBER OF COOKING ZONES	n° 1	MINIMUM POWER CABLE CROSS-SECTION	3 x 1,5 n° - mm²
ELECTRIC CABLE TYPE	H07 RN-F	IPX RATING	4
WIDTH	40 cm	DEPTH	45 cm
HEIGHT	90 cm	PACKAGE WIDTH	99 cm
PACKAGE DEPTH	47 cm	PACKAGE HEIGHT	69 cm
NET WEIGHT	21,5 kg	GROSS WEIGHT	29,5 kg
VOLUME	0,32 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	120.0 W	SENSIBLE HEAT RELEASE	520.0 W
STEAM RELEASE	306.8 g/h		

ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

INSTALLATION SCHEMES

