

716179**BP120N****TECNO74 REFRIGERATED BASE (GN1/1) - 2 DOORS
WITH R290 GAS - CM 120X65X62H**



- R290 refrigerant with low global warming potential (GWP), making the appliances eco-friendly.
- Ventilated refrigeration for an even temperature inside the base unit.
- Digital control panel.
- 50 mm thick insulation made with HCFC-free polyurethane resins.
- Automatic defrosting via electric heaters.
- Automatic condensation water disposal device.
- Easily replaceable magnetic gaskets for excellent sealing.
- AISI 304 stainless steel height-adjustable feet.
- Internal construction made with AISI 304 stainless steel.
- External construction: AISI 304 doors, drawers, side panels, worktop. AISI 430 stainless steel back panel.
- R290 refrigerant with low global warming potential (GWP), making the appliances eco-friendly.
- Ventilated refrigeration for an even temperature inside the base unit.
- Digital control panel.
- 50 mm thick insulation made with HCFC-free polyurethane resins.
- Automatic defrosting via electric heaters.
- Automatic condensation water disposal device.
- Easily replaceable magnetic gaskets for excellent sealing.
- AISI 304 stainless steel height-adjustable feet.


TECHNICAL DATA

TOTAL POWER	0,265 kW	ELECTRIC POWER	0,265 kW
FREQUENCY	50 Hz	VOLTAGE	230 ~ V
TEMPERATURE RANGE	-2÷8 °C	REFRIGERATOR POWER	189 kCal/h
GROSS CELL CAPACITY	130 lt	GAS LOAD	0,175 kg
DRAWERS	n° 0	DOORS	n° 2
DOORS / DRAWERS	n° 2 / 0	MINIMUM POWER CABLE CROSS-SECTION	3 x 1,5 n° - mm²
ELECTRIC CABLE TYPE	H07 RN-F	ELECTRICAL CONNECTION HEIGHT (H)	0 mm
ELECTRICAL CONNECTION HEIGHT (X)	1170 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-180 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	3	WIDTH	120 cm
DEPTH	65 cm	HEIGHT	62 cm
PACKAGE WIDTH	127,0 cm	PACKAGE DEPTH	73,0 cm
PACKAGE HEIGHT	80,0 cm	NET WEIGHT	68 kg
GROSS WEIGHT	83 kg	VOLUME	0,7400 m³
HARMONISED CODE	84185090		

ACCESSORIES

INSTALLATION SCHEMES


BC/BP/BPC120(140)



ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 1.5 mt
 POTENZA MAX ASSORBITA : 350 W

GAS : R 134 a

BC/BP/BPC160(175)



ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 1.5 mt
 POTENZA MAX ASSORBITA : 385 W

GAS : R 134 a

Fig.1 | Abb.1 | рис.1 - 5415.692.00