

716231

FTR4BFE7

**FREESTANDING ELECTRIC GRIDDLE WITH
BRUSHED, CHROME-PLATED, RIBBED PLATE ON
OPEN CABINET**



- Freestanding electric griddle on an open cabinet (40 cm) with a brushed chrome-plated, ribbed cooking plate to cook a variety of products: from meat to fish and vegetables.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances product grilling.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 310°C.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Removable splashback on 3 sides and cap supplied.
- Technical compartment for easy connection to the electrical network mains.

TECHNICAL DATA

Total power	3,9 kW	Electric power	3,9 kW
Frequency	50/60 Hz	Voltage	380-415 3N~ V
CAMPO_0027	0012	Cabinet dimensions	33x57,4x39,5 cm
Minimum power cable cross-section	5 x 1,5 n° - mm²	Cooking surface	35,3x56,4 cm
Electric cable type	H07 RN-F	Plate type	0014
Heating zones	n° 1	Electrical connection height (H)	660 mm
Electrical connection height (X)	321 mm	Electrical connection height (Y)	-63 mm
Foot height	155 mm	Foot adjustment	155/250 mm
IPX rating	4	Width	40 cm
Depth	70 cm	Height	90 cm
Package width	81,0 cm	Package depth	47,0 cm
Package height	115,0 cm	Net weight	44,5 kg
Gross weight	57,5 kg	Volume	0,44 m³
Harmonised code	84198180	Latent heat release	1560.0 W
Sensible heat release	1287.0 W	Steam release	2293.2 g/h

ACCESSORIES

- 120595 GRIDDLE-CLEANING SCRAPER
- 120597 SCRAPER - SPARE BLADE KIT (10 PCS)
- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 719004 TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=40CM)
- 719040 SIDE HEAT PROTECTION DEVICE
- 799503 SIDE COVERING PANEL FOR FREESTANDING MODULE
- 799506 PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.654.00