

716556

EHLD4BFE7

**FREESTANDING ELECTRIC GRIDDLE WITH
BRUSHED, CHROME-PLATED, SMOOTH PLATE AND
ELECTRONIC CONTROL ON OPEN CABINET**



- EVENHEAT Freestanding electric griddle on an open cabinet (40 cm) with electronic control and a brushed chrome-plated, smooth cooking plate to cook a variety of products: from meat to fish and vegetables.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances product grilling.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- The electronic control allows for greater precision between the set temperature and the cooking plate temperature.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- Stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Thanks to thin, flexible elements, heat is distributed with absolute precision exactly where it is needed.
- The EVENHEAT technology, patent pending, grants a real temperature across the full plate, eliminating any cold or overheated spots
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Included: removable splashback, cap and scraper.
- Technical compartment for easy connection to the electrical network mains.

TECHNICAL DATA

TOTAL POWER	4,5 kW	ELECTRIC POWER	4,5 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	CABINET DIMENSIONS	33x57,4x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm ²	COOKING SURFACE	35,3x56,4 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Brushed chrome-plated - smooth
HEATING ZONES	n° 1	ELECTRICAL CONNECTION HEIGHT (H)	660 mm
ELECTRICAL CONNECTION HEIGHT (X)	321 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-63 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	4	WIDTH	40 cm
DEPTH	70 cm	HEIGHT	90 cm
PACKAGE WIDTH	81 cm	PACKAGE DEPTH	47 cm
PACKAGE HEIGHT	114 cm	NET WEIGHT	51,2 kg
GROSS WEIGHT	61,2 kg	VOLUME	0,43 m ³
HARMONISED CODE	84198180		

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
719004	TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=40CM)
719040	SIDE HEAT PROTECTION DEVICE
799503	SIDE COVERING PANEL FOR FREESTANDING MODULE
799506	PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.648.00