

716564

EHCD12FE7

FREESTANDING ELECTRIC GRIDDLE WITH CHROME-PLATED SMOOTH PLATE AND ELECTRONIC CONTROL ON OPEN CABINET WITH EVENHEAT TECHNOLOGY



- EVENHEAT Freestanding electric griddle on an open cabinet (120 cm) with electronic control and a mirror-polished chrome-plated, smooth cooking plate recommended for cooking delicate products.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- 3 independent cooking zones.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- The electronic control allows for greater precision between the set temperature and the cooking plate temperature.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (15 mm thick) to facilitate the drainage of grease and liquids.
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- Stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Thanks to thin, flexible elements, heat is distributed with absolute precision exactly where it is needed.
- The EVENHEAT technology, patent pending, grants a real temperature across the full plate, eliminating any cold or overheated spots
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Included: removable splashback, cap and scraper.
- Technical compartment for easy connection to the electrical network mains.

TECHNICAL DATA

TOTAL POWER	13,5 kW	ELECTRIC POWER	13,5 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	CABINET DIMENSIONS	113x57,4x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²	COOKING SURFACE	113x56 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Chrome-plated - smooth
HEATING ZONES	n° 3	ELECTRICAL CONNECTION HEIGHT (H)	660 mm
ELECTRICAL CONNECTION HEIGHT (X)	1121 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-63 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	4	WIDTH	120 cm
DEPTH	70 cm	HEIGHT	90 cm
PACKAGE WIDTH	125 cm	PACKAGE DEPTH	82 cm
PACKAGE HEIGHT	112 cm	NET WEIGHT	137 kg
GROSS WEIGHT	150 kg	VOLUME	1,13 m ³
HARMONISED CODE	84198180		

ACCESSORIES

- 120595 GRIDDLE-CLEANING SCRAPER
- 120597 SCRAPER - SPARE BLADE KIT (10 PCS)
- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 719006 TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=120CM)
- 719040 SIDE HEAT PROTECTION DEVICE
- 799503 SIDE COVERING PANEL FOR FREESTANDING MODULE
- 799506 PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.648.00